

Kodak i2800 Scanner

www.kodak.com/go/docimaging



Data collected from materials published by the respective manufacturer and is subject to technical change without notice. December 2010 ©Kodak, 2010. Kodak is a trademark of Kodak



The i2000 Series Scanners continue to deliver the “difference you’ve been looking for”.

Ease of use

Design

- Integrated extendable exit tray
- Straight-through paper path
- Operator Control Panel

Performance = Throughput + Reliability + Quality

- **Throughput** = Ease of use + Automation +Speed
 - o Stow-or-go design
 - o Instant on DUAL LED lamps
 - o Automated image processing: Perfect Page
 - o 70ppm @200dpi and 300dpi B&W
 - o 60ppm @200dpi Color
 - o 40ppm @300 dpi Color

Smart Touch

- Scan, manage, send
- Ability to map to other applications
- Scan to **Microsoft SharePoint**
- Scan to web-based email clients, i.e. **Gmail, Yahoo!** and **Hotmail**

Reliability = Paper handling + Uptime + Support

- o Scan onion skin to embossed hard cards
- o Manufacturing – Out of Box Quality
- o 3 yr Warranty

Quality = Image to Image; Scanner to scanner

- o Advanced image processing features yields high quality images and data supporting OCR applications

Total Cost Of Ownership

- Advanced image processing included
- Smart Touch scanning included
- 3yr Warranty

Relevant Links

- www.kodak.com/go/i2000seriescanners
- www.kodak.com/go/perfectpage
- www.kodak.com/go/smarttouch

Kodak
Service & Support

				Kodak	Avision	Canon	Fujitsu	Visioneer/ Xerox
				i2800	AV220D2+	DR 6010C	fi-6140/fi-6240	DocuMate 3460
U.S. List Price				\$1,895	\$1,189	\$3,495	fi-6140: \$1,995 fi-6240: \$2,495	DocuMate 3460 VRS Basic: \$1,595 DocuMate 3460 VRS Pro: \$1,895
Scanning speed	Portrait Letter	B&W:	@ 200 dpi	70 ppm/140 ipm	60 ppm/120 ipm	60 ppm/120 ipm	60 ppm/120 ipm	60 ppm/120 ipm
			@ 300 dpi	70 ppm/140 ipm	50 ppm/100 ipm	N/A	40 ppm/80 ipm	N/A
		Color:	@ 200 dpi	60 ppm/120 ipm	60 ppm/120 ipm	60 ppm/120 ipm	40 ppm/80 ipm	60 ppm/120 ipm (150 dpi)
			@ 300 dpi	40 ppm/80 ipm	50 ppm/100 ipm	N/A	40 ppm/80 ipm	N/A
Recommended daily volume				6,000 sheets	3,000 sheets	7,500 sheets	4,000 sheets	6,500 sheets
Optical resolution				600 dpi	600 dpi	600 dpi	600 dpi	600 dpi
Sensor				CCD	CCD	CMOS/CIS	CCD	CCD
Illumination				Dual LED	CCFL	LED	CCFL	CCFL
Paper (ADF)	ADF capacity			100 sheets	50 sheets	100 sheets	50 sheets	100 sheets
	Straight-through paper path			Yes	Yes	Yes	Yes	Yes
	Maximum scan size			8.5 x 34 in. (216 mm x 863 mm)	8.5 x 14 in. (216 x 356 mm)	8.6 x 14 in. (218 x 356 mm)	8.5 x 14 in. (216 x 356 mm)	8.5 x 38 in. (216 x 965 mm)
	Minimum scan size			2 x 2.5 in. (51 x 64 mm)	2 x 3 in. (51 x 58 mm)	2.1 x 2.8 in. (53 x 71 mm)	2 x 3 in. (51 x 76 mm)	2 x 3.5 in. (51 x 89 mm)
Interface				Certified USB 2.0	USB 2.0	USB 2.0, SCSI III	USB 2.0	USB 2.0
Drivers				TWAIN, ISIS, WIA (included), Linux SANE	TWAIN and ISIS	TWAIN and ISIS	TWAIN and ISIS	TWAIN, ISIS, WIA
Multi-feed detection				Ultrasonic	Ultrasonic	Ultrasonic	Ultrasonic	Ultrasonic
Long document mode				34 in (863 mm)	36 in. (914 mm)	N/A	122 in (mm)	38 in. (965 mm)
Auto color detection				Yes	Yes	Yes	Yes	Yes
Unique Features	Ease of use			Kodak's Smart Touch Pre-configured job functions	Job Button	Job Button	Job Button	Visioneer OneTouch
	Image processing			Kodak's Perfect Page Kofax VRS Compatible	AVScan Kofax VRS	Canon CapturePerfect Kofax VRS Compatible	ScandAll, Kofax VRS Compatible	Kofax VRS
	Flatbed			Yes – Optional	N/A	Yes - Optional	N/A – fi-6140 Yes – fi-6240	N/A
	Streak filter			Yes	N/A	N/A	N/A	N/A
	Dual Stream: Color /B&W or Grayscale and B&W images			Yes – Kodak creates two independent images	N/A	MultiStream (2 nd image created from 1 st image)	MultiStream (2 nd image created from 1 st image)	N/A
	Tilts for optimal scanning position			Yes	N/A	N/A	N/A	N/A
Bundled software				Kodak's Smart Touch Kodak Capture Desktop Software Nuance ScanSoft PaperPort and OmniPage	AVScan, Nuance PaperPort, Kofax VRS	Canon CapturePerfect, Adobe Acrobat, Kofax VRS	ScandAll, Kofax VRS, Adobe Acrobat	Kofax VRS, Nuance ScanSoft Paperport and Omnipage, EMC Captiva QuickScan Pro Demo
Dimensions (H x W x D)				9.7 x 13 x 6.3 in. (246 x 330 x 162 mm)	6.4 x 13.3 x 6.6 in. (163x 338 x 168 mm)	7.3 x 12.5 x 10.9 in. (185 x 318 x 277 mm)	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm) 11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)	6.4 x 13.3 x 6.5 in. (163x 338 x 165 mm)
Weight				12 lbs (5.5 kg)	7.9 lbs (3.6 kg)	14.31 lbs (6.5 kg)	9.24 lbs. (4.2 kg) 19.36 lbs. (8.8 kg)	9.44 lbs (4.3 kg)
Warranty				3 Years Limited Warranty	1 Year Exchange	1 Year Exchange	1 Year Exchange	1 Year